






## OUTDOOR HOUSING

- \* Powder coated light weight aluminium construction
- \* IP53 rated with vandal resistant screen protection
- \* Heating / cooling in response to ambient temperatures
- \* User replaceable cartridge style air filtration
- \* Wall, ceiling or back-to-back mountable
- \* Wide range from 32" to 80" screens
- \* Perfect fit to screen build quality
- \* Supports up to 60kg
- \* Colour black











## Main Housing











ODH0 30" to 32" ODH1 33" to 57" ODH2 58" to 70" ODH3 80"





## Notes:

- \* This is not a refrigeration unit, therefore in hot conditions consideration should be given to the performance of the screen used and positioning in direct sunlight should be avoided.
- \* There is a dedicated charge for carriage on this item.
- \* UNICOL stainless steel columns and weather proof fastenings should be used with this product.
- \* Housings are made for each specific screen please supply make and model when ordering.

## **LCD Outdoor Housing**

All are constructed in 1050 grade aluminium and utilise high quality temperature control components within. Screen viewing panels in impact resistant polycarbonate are incorporated as standard, toughened or laminated glass is also available as an option.

- \* Circulating fans and heater fitted as standard
- \* Controlled heating 0 to 60 degrees C
- \* Controlled Cooling 0 to 60 degrees C
- \* Replaceable dust filter fitted as standard
- \* Can be supplied for wall or ceiling mounting
- \* Back to Back versions also available
- \* Anti-reflective screen available
- \* Large range from 30" to 80"
- \* Supports up to 60kg
- \* Colour black

UNICOL Willi-Grasser-Str. 15 D-91056 Erlangen +49(0)9131 9405 800 info@unicol.de www.unicol.de









